Panasonic

CJ-HDR416A

16 CH HDCVI 4 SATA HDD Analog Digital Video Recorder




Key Features

- 16 CH with 720P/1080P recording playback and live view
- H.264 video compression
- 1/4/9/16 CH synchronous real time playback
- HDMI/VGA/TV simultaneous video output
- Supports 4 SATA HDDs up to 8TB for each disk, 3 USBs
- Digital zoom during live & playback
- iPhone, iPad, Android

Standard Accessories

•	Quick Start Guide1 pc
•	Important Safety Instructions1 pc
•	CD 1 nc

Appearance



440

Specifications

Specifications			
Model		CJ-HDR416A	
Video/Audio IF			
Video Input		16 CH, BNC	
Type	HDCVI	720P/1080P	
.,,,,	Analog	PAL/NTSC	
Video Output		2 HDMI, 1 VGA, 1 BNC	
Audio Input		4 CH, BNC	
Audio Output		1 CH, BNC	
Two-way Talk		1 Mic In, 1 Mic Out, BNC	
Display			
Output Resolution		1920×1080, 1280×1024, 1280×720, 1024×768	
Multiscreen Mode		1/4/8/9/16	
Privacy Masking		4 rectangular zones (each camera)	
OSD		Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Video/Audio F	ormat		
Video/Audio Co	mpression	H.264/G.711a	
Record	Main Stream	1080P/1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps)	
Rate*	Sub Stream	D1/CIF/QCIF (1~15fps)	
Bit Rate		1Kbps~6144Kbps per channel	
Record Mode		Manual, Schedule (Regular, Continuous), Alarm, MD, Stop	
Record Interval		1~60 min (default: 60 min), Pre-record: 0~30 sec, Post-record: 10~300 sec	
Alarm/Event			
Alarm Input		16 CH	
Relay Output		6 CH	
Trigger Events		Recording, PTZ, Tour, Email, FTP, Alarm Output, Snapshot, Buzzer, Show Message, Alarm Upload, Video Matrix and Log	
Video Detection		Motion Detection, MD Zones: 396 (22x18)/330 (22x15), Video Loss, Tampering	
Playback & Ba	ckup		
Sync Playback		1/4/9/16	
Search Mode		Time/Date, Alarm, MD and Exact Search (accurate to second)	
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom, Customized playback, Splice playback	
Backup Mode		USB Device/Network	
Network			
Network Interface Network Functions Max. User Access		RJ-45 port (1000M)	
		HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, SNMP, EZ Remote	
		128 users	
Mobile Device		iPhone, iPad, Android	
HDD			
Туре		4 SATA ports, up to 8TB for each disk	
External Interfa	ace	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
USB Interface		3 ports (2 rear), 1 USB2.0, 2 USB3.0	
RS232		1 port, for PC communication & keyboard	
RS485		1 port, for PTZ control	
RS422		1 port, for PTZ control	
General Specif	fications	1 - 1 - 2 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3	
Power Supply		AC 100~240V, 50/60 Hz	
Power Consumption		<30W (without HDD)	
Working Environment		-10°C~+55°C/0%~90%RH	
		1.5U, 440mm×418.7mm×76mm	
Dimension (Wx	DXII)	· · · · · · · · · · · · · · · · · · ·	
Weight	For shannal 1	4.73kg (without HDD) channel 5, channel 9 and channel 13, the change of the frame rate to 16fps or	

 For channel 1, channel 5, channel 9 and channel 13, the change of the frame rate to 16fps or more at 1080P, will update the frame rate settings of other channels to 15fps.

- Recommended to schedule a weekly reboot.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

Important

- Safety Precaution: Carefully read the user's manual before using this product.

DISTRIBUTED BY: